



## Putoline Product recommendation

### Beta Evo Evo 2T 125 (2015 and after)

Recommended product  
Good alternatives

#### ENGINE, BETA

MX 9

TT Trial Pro Scented

#### TRANSMISSION, 6

We are unable to give a standard recommendation for this component. Please contact our service department.

#### HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 40 hours

DOT 4 Brake Fluid

Normal, Check every 1000 km/ 40 hours

#### HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 40 hours

DOT 4 Brake Fluid

Normal, Check every 1000 km/ 40 hours

#### GREASE POINTS/NIPPLES

White Action Grease + PTFE

Racing Grease

#### COOLING SYSTEM

0,63 liter Capacity

0,53 liter Capacity

Ultracool 12

Normal, Check every 1000 km/ 40 hours

Normal, Change every 2000 km/ 80 hours

Coolant NF

Normal, Check every 1000 km/ 40 hours

Normal, Change every 2000 km/ 80 hours

#### FRONT FORK LEFT

125 mm Capacity

Formula GP 5W, 5W

Normal, Change every 2000 km/ 80 hours

Initial service, Change every 1000 km/ 40 hours

HPX R 5W, 5W

Normal, Change every 2000 km/ 80 hours

Initial service, Change every 1000 km/ 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

**FRONT FORK RIGHT**

65 mm Capacity

Formula GP 5W, 5W

Normal, Change every 2000 km/ 80 hours

Initial service, Change every 1000 km/ 40 hours

Good alternatives

HPX R 5W, 5W

Normal, Change every 2000 km/ 80 hours

Initial service, Change every 1000 km/ 40 hours

Recommended product

**SHOCK ABSORBER REAR**

Formula GP 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.