

## Putoline Product recommendation

## Beta Xtrainer Xtrainer 300 (2016-2017)

Recommended product Good alternatives

**ENGINE + AUTOMATIC LUBRICATION** 

<u>MX 9</u>

<u>MX 7</u>

<u>MX 5</u>

TRANSMISSION, 6

0,85 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-40, 10W-40

Normal, Change every 30 hours

Initial service, Change every 3 hours

Good alternatives <u>Ester Tech Off Road 4+ 10W-40, 10W-40</u>

Normal, Change every 30 hours Initial service, Change every 3 hours

**HYDRAULIC BRAKE SYSTEM** 

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid,

Normal, Check every 30 hours Initial service, Check every 3 hours

**HYDRAULIC CLUTCH SYSTEM** 

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid.

Normal, Check every 30 hours Initial service, Check every 3 hours

**COOLING SYSTEM** 

1,3 liter Capacity

Recommended product | <u>Ultracool 12</u>,

Normal, Check every 30 hours

Initial service, Check every 3 hours

Good alternatives Coolant NF,

Normal, Check every 30 hours Initial service, Check every 3 hours

FRONT FORK

Recommended product | 0,5 liter Capacity | Formula GP 5W

Normal, Check every 30 hours

Good alternatives | HPX R 5W

Normal, Check every 30 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.