



Putoline Product recommendation

BMW K series K 1200 RS (1996-2000)

Recommended product **ENGINE**
N-TECH® Pro R+ 5W-40, 10W-40, 15W-50, 10W-30

Good alternatives
Normal, Check every 3000 km
Normal, Change every 10000 km/ 12 months
Ester Tech 4+ 10W-40, 15W-50

Normal, Check every 3000 km
Normal, Change every 10000 km/ 12 months
Sport 4R 10W-40, 15W-50, 10W-30
Normal, Check every 3000 km
Normal, Change every 10000 km/ 12 months
Super DX4 10W-40
Normal, Check every 3000 km
Normal, Change every 10000 km/ 12 months

Recommended product **SHAFT DRIVE**
0,25 liter Capacity
SP Gear Oil 75W-90

Good alternatives
Normal, Change every 15000 km/ 12 months
RS 75 75/80W
Normal, Change every 15000 km/ 12 months
Heavy Gear 80W-90
Normal, Change every 15000 km/ 12 months

Recommended product **TRANSMISSION, 5/1**
0,8 liter Capacity
SP Gear Oil 75W-90

Good alternatives
Normal, Change every 20000 km/ 12 months
RS 75 75/80W
Normal, Change every 20000 km/ 12 months
Heavy Gear 80W-90
Normal, Change every 20000 km/ 12 months

Recommended product **HYDRAULIC BRAKE SYSTEM**
0,5 liter Capacity
Ultimate Racing Brake Fluid

Good alternatives
Normal, Check every 15000 km
Normal, Change every 12 months
DOT 4 Brake Fluid
Normal, Check every 15000 km
Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

COOLING SYSTEM

Ultracool 12

Normal, Change every 24 months

Coolant NF

Normal, Change every 24 months

Recommended product

Good alternatives

FRONT FORK LEFT

0,35 liter Capacity

Formula GP 10W

Normal, Change every 15000 km/ 12 months

HPX R 10W

Normal, Change every 15000 km/ 12 months

Recommended product

Good alternatives

FRONT FORK RIGHT

0,4 liter Capacity

Formula GP 10W

Normal, Change every 15000 km/ 12 months

HPX R 10W

Normal, Change every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.