

## Putoline Product recommendation

# Derbi GPR GPR 50 (1997-2003)

### **ENGINE + AUTOMATIC LUBRICATION**

1,1 liter Capacity

Recommended product Good alternatives

RS 959

TT Sport

TT Scooter +

TT Scooter

TT Scooter Scented

TRANSMISSION, 6

0,65 liter Capacity

Recommended product

RS 75 75/80W

Normal, Check every 3000 km

Normal, Change every 3000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

Recommended product

Ultimate Racing Brake Fluid

Normal, Change every 12 months

Good alternatives **DOT 4 Brake Fluid** 

Normal, Change every 12 months

#### **GREASE POINTS/NIPPLES BEARINGS**

We are unable to give a standard recommendation for this component. Please contact our service department.

#### **COOLING SYSTEM**

0,85 liter Capacity

Recommended product

Ultracool 12

Normal, Change every 12 months

Good alternatives Coolant NF

Normal, Change every 12 months

## FRONT FORK LEFT

Recommended product

Good alternatives

0,18 liter Capacity

HPX R 5W, 10W Normal, Check every 2000 km

Normal, Change every 6000 km

Light Fork

Normal, Check every 2000 km

Normal, Change every 6000 km

Medium Fork

Normal, Check every 2000 km

Normal, Change every 6000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

#### FRONT FORK RIGHT

0,15 liter Capacity HPX R 5W, 10W

Normal, Check every 2000 km

Normal, Change every 6000 km

Light Fork

Normal, Check every 2000 km

Normal, Change every 6000 km

Medium Fork

Normal, Check every 2000 km Normal, Change every 6000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.