



Putoline Product recommendation

Husaberg FE FE 350 (2013-2013)

ENGINE/TRANSMISSION

1,2 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 1 race/ 15 hours

Initial service, Change every 1 hours

Good alternatives N-TECH® Pro R+ Off Road 10W-60, 10W-60

Normal, Change every 1 race/ 15 hours

Initial service, Change every 1 hours

Ester Tech Off Road 4+ 10W-50, 10W-60, 10W-60

Normal, Change every 1 race/ 15 hours

Initial service, Change every 1 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Change every 12 months

Good alternatives DOT 4 Brake Fluid

Normal, Change every 12 months

DOT 5.1 Brake Fluid

Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Change every 12 months

Good alternatives DOT 4 Brake Fluid

Normal, Change every 12 months

DOT 5.1 Brake Fluid

Normal, Change every 12 months

COOLING SYSTEM

1,2 liter Capacity

Recommended product Ultracool 12.

Normal, Check every 15 hours/ each race

Initial service, Check every 1 hours

Good alternatives Coolant NF.

Normal, Check every 15 hours/ each race

Initial service, Check every 1 hours

FRONT FORK

607 CM3 Capacity

Recommended product HPX R 4W, 4W

Normal, Change every 45 hours

Initial service, Change every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

SHOCK ABSORBER REAR

HPX R 2.5W

Normal, Change every 45 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.