Putoline Product recommendation

Husaberg FE FE 450 (2013-2013)

ENGINE/TRANSMISSION

1,5 liter Capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-50, 10W-50
Normal, Change every 1 race/ 15 hours
Initial service, Change every 1 hours

Good alternatives
N-TECH® Pro R+ Off Road 10W-60, 10W-60
Normal, Change every 1 race/ 15 hours
Initial service, Change every 1 hours

Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-60, 10W-60
Normal, Change every 1 race/ 15 hours
Initial service, Change every 1 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Change every 12 months

Good alternatives
DOT 4 Brake Fluid
Normal, Change every 12 months

DOT 5.1 Brake Fluid
Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Change every 12 months

Good alternatives
DOT 4 Brake Fluid
Normal, Change every 12 months

DOT 5.1 Brake Fluid
Normal, Change every 12 months

COOLING SYSTEM

1,2 liter Capacity

Recommended product
Ultracool 12,
Normal, Check every 15 hours/ each race
Initial service, Check every 1 hours

Good alternatives
Coolant NF,
Normal, Check every 15 hours/ each race
Initial service, Check every 1 hours

FRONT FORK

607 CM3 Capacity

Recommended product
HPX R 4W, 4W
Normal, Change every 45 hours
Initial service, Change every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Recommended product

SHOCK ABSORBER REAR
HPX R 2.5W
Normal, Change every 45 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.