Putoline Product recommendation

KTM 300 300 EXC (2010-2012)

	ENGINE
Recommended product	MX 9
Good alternatives	MX 7
	MX 5
	TRANSMISSION, 6
	0,8 liter Capacity
Recommended product	Boxer 4 15W-50, 15W-50
	Normal, Change every 40 hours/ 280 liter consumed fuel
	Initial service, Change every 10 hours/ 70 liter consumed fuel
Good alternatives	N-TECH® Pro R+ Off Road 15W-50, 15W-50
	Normal, Change every 40 hours/ 280 liter consumed fuel
	Initial service, Change every 10 hours/ 70 liter consumed fuel
	Ester Tech Off Road 4+ 15W-50, 15W-50
	Normal, Change every 40 hours/ 280 liter consumed fuel
	Initial service, Change every 10 hours/ 70 liter consumed fuel
	HYDRAULIC BRAKE SYSTEM
	0-0 liter Capacity
Recommended product	Ultimate Racing Brake Fluid
	Normal, Change every 12 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Change every 12 months
	DOT 5.1 Brake Fluid
	Normal, Change every 12 months
	HYDRAULIC CLUTCH SYSTEM
	0-0 liter Capacity
Recommended product	Hydraulic Clutch Fluid
	Normal, Change every 12 months
	COOLING SYSTEM
	1,3 liter Capacity
Recommended product	Ultracool 12
Good alternatives	Coolant NF
	FRONT FORK
	625 CM3 Capacity
Recommended product	Formula GP 5W, 5W
	Normal, Change every 40 hours
	Initial service, Change every 10 hours/ 1 race
Good alternatives	HPX R 5W, 5W
	Normal, Change every 40 hours
	Initial service, Change every 10 hours/ 1 race

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

Recommended product

SHOCK ABSORBER REAR
HPX R 2.5W
Normal, Change every 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.