



## Putoline Product recommendation

### KTM 400 400 MXC (2005-2006)

#### ENGINE/TRANSMISSION

1,25 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 100 liter consumed fuel/ 15 hours

Good alternatives

Initial service, Change every 3 hours/ 20 liter consumed fuel

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 100 liter consumed fuel/ 15 hours

Initial service, Change every 3 hours/ 20 liter consumed fuel

#### HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid

Normal, Change every 12 months

#### HYDRAULIC CLUTCH SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

#### COOLING SYSTEM

1 liter Capacity

Recommended product Ultracool 12

Good alternatives Coolant NF

#### FRONT FORK

Formula GP 5W

Recommended product Normal, Change every 12 months

Good alternatives HPX R 5W

Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.