



## Putoline Product recommendation

### Argo Vanguard 6x6 Vanguard2 (2004-2007)

#### **ENGINE, BRIGGS & STRATTON VANGUARD**

1,6 liter Capacity

Recommended product Ester Tech Quad RF4+ 10W-40, 10W-40

Normal, Change every 50 hours

Good alternatives Initial service, Change every 8 hours

Quad RF4 10W-40, 10W-40

Normal, Change every 50 hours

Initial service, Change every 8 hours

#### **TRANSMISSION, 2/1**

0,85 liter Capacity

Recommended product SP Gear Oil 75W-90, 75W-90

Normal, Check every 50 hours

Initial service, Check every 2 hours

Normal, Change every 100 hours

Good alternatives Initial service, Change every 20 hours

Heavy Gear 80W-90, 80W-90

Normal, Check every 50 hours

Initial service, Check every 2 hours

Normal, Change every 100 hours

Initial service, Change every 20 hours

#### **HYDRAULIC BRAKE SYSTEM**

0-0 liter Capacity

Recommended product DOT 5 Silicone Brake Fluid

Normal, Check every 50 hours

Normal, Change every 150 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.