



Putoline Product recommendation

Beta Evo Evo 2T 250 (2014-2014)

| | |
|---------------------|--|
| Recommended product | ENGINE, BETA <u>MX 9</u> |
| Good alternatives | <u>TT Trial Pro Scented</u> |
| | TRANSMISSION, 6 0,55 liter Capacity |
| Recommended product | <u>RS 75 75/80W, 75-80W</u> Normal, Change every 1000 km/ 40 hours Initial service, Change every 5 hours |
| | HYDRAULIC BRAKE SYSTEM 0-0 liter Capacity |
| Recommended product | <u>Ultimate Racing Brake Fluid</u> Normal, Check every 1000 km/ 40 hours |
| Good alternatives | <u>DOT 4 Brake Fluid</u> Normal, Check every 1000 km/ 40 hours |
| | HYDRAULIC CLUTCH SYSTEM 0-0 liter Capacity |
| Recommended product | <u>Ultimate Racing Brake Fluid</u> Normal, Check every 1000 km/ 40 hours |
| Good alternatives | <u>DOT 4 Brake Fluid</u> Normal, Check every 1000 km/ 40 hours |
| | GREASE POINTS/NIPPLES |
| Recommended product | <u>White Action Grease + PTFE</u> |
| Good alternatives | <u>Racing Grease</u> |
| | COOLING SYSTEM 0,53 liter Capacity 0,42 liter Capacity |
| Recommended product | <u>Ultracool 12</u> Normal, Check every 1000 km/ 40 hours Normal, Change every 2000 km/ 80 hours |
| Good alternatives | <u>Coolant NF</u> Normal, Check every 1000 km/ 40 hours Normal, Change every 2000 km/ 80 hours |
| | FRONT FORK LEFT 125 mm Capacity |
| Recommended product | <u>HPX R 7.5W, 7.5W</u> Normal, Change every 2000 km/ 80 hours Initial service, Change every 1000 km/ 40 hours |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

FRONT FORK RIGHT

65 mm Capacity

HPX R 7.5W, 7.5W

Normal, Change every 2000 km/ 80 hours

Initial service, Change every 1000 km/ 40 hours

Recommended product

SHOCK ABSORBER REAR

Formula GP 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.