



## Putoline Product recommendation

### Beta RR RR 4T Enduro 450 (2012-2012)

#### ENGINE

0,85 liter Capacity

Recommended product

Boxer 4 15W-50, 15W-50

Normal, Change every 30 hours/ 200 liter consumed fuel

Good alternatives

Initial service, Change every 3 hours/ 20 liter consumed fuel

N-TECH® Pro R+ Off Road 15W-50, 15W-50

Normal, Change every 30 hours/ 200 liter consumed fuel

Initial service, Change every 3 hours/ 20 liter consumed fuel

Ester Tech Off Road 4+ 15W-50, 15W-50

Normal, Change every 30 hours/ 200 liter consumed fuel

Initial service, Change every 3 hours/ 20 liter consumed fuel

#### TRANSMISSION, 6

0,85 liter Capacity

Recommended product

N-TECH® Pro R+ Off Road 10W-40, 10W-40

Normal, Change every 30 hours/ 200 liter consumed fuel

Good alternatives

Initial service, Change every 3 hours/ 20 liter consumed fuel

Ester Tech Off Road 4+ 10W-40, 10W-40

Normal, Change every 30 hours/ 200 liter consumed fuel

Initial service, Change every 3 hours/ 20 liter consumed fuel

Off Road 4 10W-40, 10W-40

Normal, Change every 30 hours/ 200 liter consumed fuel

Initial service, Change every 3 hours/ 20 liter consumed fuel

#### HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 15 hours

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 15 hours

#### HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 15 hours

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 15 hours

#### COOLING SYSTEM

1,3 liter Capacity

Recommended product

Ultracool 12

Good alternatives

Coolant NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

**FRONT FORK**

150 mm Capacity

HPX R 2.5W

Normal, Check every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.