



## Putoline Product recommendation

### Buell M2 Cyclone M2 Cyclone (2000-2004)

#### ENGINE

2,37 liter Capacity

0,12 liter Filter capacity

Recommended product Genuine V-Twin 20W-50, SAE 50

Normal, Check every 4000 km

Good alternatives

Normal, Change every 8000 km/ 12 months

Formula V-Twin 20W-50, 20W-50

Normal, Check every 4000 km

Normal, Change every 8000 km/ 12 months

#### TRANSMISSION, 5

0,95 liter Capacity

Recommended product SP Gear Oil 75W-90

Normal, Check every 4000 km

Normal, Change every 8000 km

#### HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid

Normal, Check every 8000 km/ 12 months

Normal, Change every 24 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 8000 km/ 12 months

Normal, Change every 24 months

#### FRONT FORK

472-473 CM3 Capacity

Recommended product HPX R 20W

Normal, Change every 32000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.