



## Putoline Product recommendation

### Casalini M series M14 (2014 and after)

Recommended product	<b>ENGINE, MITSUBISHI L2E</b> 2,5 liter Capacity <u>ATV Farm Oil 15W-40</u>
Recommended product	<b>FINAL GEAR FRONT, 1/1</b> 0,75 liter Capacity <u>SP Gear Oil 75W-90</u> Normal, Change every 20000 km
Recommended product	<b>HYDRAULIC BRAKE SYSTEM</b> <u>Ultimate Racing Brake Fluid</u> Normal, Change every 30000 km/ 24 months
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 30000 km/ 24 months
Recommended product	<b>COOLING SYSTEM</b> 1,2 liter Capacity <u>Ultracool 12</u> Normal, Change every 30000 km/ 24 months
Good alternatives	<u>Coolant NF</u> Normal, Change every 30000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.