



Putoline Product recommendation

Christini AWD AWD 450 EXPLORER / DS / SM (2015 and after)

ENGINE

0,87 liter Capacity

0,7 liter Capacity

0,3 liter Filter capacity

Recommended product N-TECH® Pro R+ Off Road 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours/ after the first break-in ride

Second change only, Change every 1500 km

Good alternatives Ester Tech Off Road 4+ 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours/ after the first break-in ride

Second change only, Change every 1500 km

Off Road 4 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours/ after the first break-in ride

Second change only, Change every 1500 km

TRANSMISSION MANUAL, 6

900 CM3 Capacity

850 CM3 Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours

Second change only, Change every 1500 km

Good alternatives Ester Tech Off Road 4+ 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours

Second change only, Change every 1500 km

Off Road 4 10W-40, 10W-40, 10W-40

Normal, Change every 3000 km

Initial service, Change every 150 km/ 10 hours

Second change only, Change every 1500 km

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid,

Normal, Check every 1500 km

Initial service, Check every 150 km/ 10 hours/ after the first break-in ride

Good alternatives DOT 4 Brake Fluid,

Normal, Check every 1500 km

Initial service, Check every 150 km/ 10 hours/ after the first break-in ride

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

COOLING SYSTEM

1,2 liter Capacity

1,11 liter Capacity

Ultracool 12, ..

Initial service, Check every 3 months

Normal, Change every 9000 km

Initial service, Change every 22000 km/ 6 months

Second change only, Change every 3500 km

Good alternatives

Coolant NF, ..

Initial service, Check every 3 months

Normal, Change every 9000 km

Initial service, Change every 22000 km/ 6 months

Second change only, Change every 3500 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.