



Putoline Product recommendation

Dinli DL 702 DL 702 (2008 and after)

ENGINE

3,5 liter Capacity

3,3 liter Capacity

Recommended product

N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 2000 km/ 6 months/ 100 hours

Initial service, Change every 200 km/ 10 hours

Good alternatives

N-TECH® Pro R+ Off Road 15W-50, 15W-50

Normal, Change every 2000 km/ 6 months/ 100 hours

Initial service, Change every 200 km/ 10 hours

Ester Tech Quad RF4+ 10W-40, 10W-40

Normal, Change every 2000 km/ 6 months/ 100 hours

Initial service, Change every 200 km/ 10 hours

Quad RF4 10W-40, 10W-40

Normal, Change every 2000 km/ 6 months/ 100 hours

Initial service, Change every 200 km/ 10 hours

ATV Farm Oil 15W-40, 15W-40

Normal, Change every 2000 km/ 6 months/ 100 hours

Initial service, Change every 200 km/ 10 hours

DIFFERENTIAL FRONT

150 CM3 Capacity

Recommended product

SP Gear Oil 75W-90

Normal, Check every 2000 km/ 6 months/ 100 hours

Normal, Change every 24 months

Good alternatives

Heavy Gear 80W-90

Normal, Check every 2000 km/ 6 months/ 100 hours

Normal, Change every 24 months

FINAL GEAR

310 CM3 Capacity

Recommended product

SP Gear Oil 75W-90

Normal, Check every 2000 km/ 6 months/ 100 hours

Normal, Change every 12 months

Good alternatives

Heavy Gear 80W-90

Normal, Check every 2000 km/ 6 months/ 100 hours

Normal, Change every 12 months

HYDRAULIC BRAKE SYSTEM

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 3 months/ 50 hours

Normal, Change every 24 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 1000 km/ 3 months/ 50 hours

Normal, Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

COOLING SYSTEM

1,6 liter Capacity

0,35 liter Capacity

Ultracool 12

Normal, Check every 1000 km/ 3 months/ 50 hours

Normal, Change every 24 months

Coolant NF

Normal, Check every 1000 km/ 3 months/ 50 hours

Normal, Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.