



Putoline Product recommendation

Ducati 1199 Panigale R Panigale R (2016-2017)

ENGINE/TRANSMISSION

3,7 liter Capacity

Recommended product N-TECH® Pro R+ 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 12 months

Good alternatives Ester Tech 4+ 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 12 months

Sport 4R 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 24 months

Good alternatives DOT 4 Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 24 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 24 months

Good alternatives DOT 4 Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 24 months

COOLING SYSTEM

2,3 liter Capacity

Recommended product Ultracool 12

Normal, Check every 12000 km/ 12 months

Normal, Change every 48000 km/ 36 months

Good alternatives Coolant NF

Normal, Check every 12000 km/ 12 months

Normal, Change every 48000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

FRONT FORK

155 CM3 Capacity

ATF

Normal, Change every 36 months

Formula GP 5W

Normal, Change every 36 months

HPX R 5W

Normal, Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.