Putoline Product recommendation

Ducati 1199 Panigale 1199 Panigale R (2012-2012)

ENGINE/TRANSMISSION

3,7 liter Capacity

Recommended product	N-TECH® Pro R+ 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30 Normal, Change every 12000 km/ 12 months Initial service, Change every 1000 km/ 6 months
Good alternatives	Ester Tech 4+ 10W-40, 10W-40, 15W-50, 15W-50 Normal, Change every 12000 km/ 12 months Initial service, Change every 1000 km/ 6 months
	Sport 4R 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30, 20W-50, 20W-50 Normal, Change every 12000 km/ 12 months Initial service, Change every 1000 km/ 6 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product	Ultimate Racing Brake Fluid Normal, Change every 24 months
Good alternatives	DOT 4 Brake Fluid Normal, Change every 24 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product	Ultimate Racing Brake Fluid Normal, Change every 24 months
Good alternatives	DOT 4 Brake Fluid Normal, Change every 24 months

GREASE POINTS/NIPPLES

Recommended product	White Action Grease + PTFE Normal, Change every 12000 km/ 12 months
Good alternatives	Racing Grease Normal, Change every 12000 km/ 12 months

COOLING SYSTEM

2,3 liter Capacity

Recommended product	Ultracool 12 Normal, Change every 36 months
Good alternatives	Coolant NF Normal, Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

FRONT FORK
155 CM3 Capacity

Recommended product	ATF Normal, Change every 36 months
Good alternatives	Formula GP 5W Normal, Change every 36 months HPX R 5W Normal, Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.