



Putoline Product recommendation

Ducati ST ST3 (2005-2007)

ENGINE/TRANSMISSION

3,9 liter Capacity

Recommended product N-TECH® Pro R+ 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30

Normal, Change every 12000 km/ 12 months

Good alternatives

Initial service, Change every 1000 km/ 6 months

Ester Tech 4+ 10W-40, 10W-40, 15W-50, 15W-50

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 6 months

Sport 4R 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30, 20W-50, 20W-50

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 6 months

Formula V-Twin 20W-50, 20W-50

Normal, Change every 12000 km/ 12 months

Initial service, Change every 1000 km/ 6 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Change every 36000 km/ 36 months

Good alternatives

DOT 4 Brake Fluid

Normal, Change every 36000 km/ 36 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Change every 36000 km/ 36 months

Good alternatives

DOT 4 Brake Fluid

Normal, Change every 36000 km/ 36 months

GREASE POINTS/NIPPLES

White Action Grease + PTFE

Recommended product

Normal, Change every 12000 km/ 12 months

Good alternatives

Racing Grease

Normal, Change every 12000 km/ 12 months

COOLING SYSTEM

2,5 liter Capacity

Recommended product

Ultracool 12

Normal, Change every 36000 km/ 36 months

Good alternatives

Coolant NF

Normal, Change every 36000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

FRONT FORK

504 CM3 Capacity

ATF

Normal, Change every 36000 km/ 36 months

Formula GP 5W

Normal, Change every 36000 km/ 36 months

HPX R 5W

Normal, Change every 36000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.