



## Putoline Product recommendation

### Husaberg FS FS 650 c (2005-2008)

#### ENGINE/TRANSMISSION

1 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 15 hours

Good alternatives

First change only, Change every 3 hours

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 15 hours

First change only, Change every 3 hours

#### HYDRAULIC BRAKE SYSTEM

Recommended product DOT 5.1 Brake Fluid

Normal, Check every 15 hours

Normal, Change every 12 months

#### HYDRAULIC CLUTCH SYSTEM

Recommended product 0-0 liter Capacity

Hydraulic Clutch Fluid

Normal, Check every 15 hours

#### COOLING SYSTEM

Recommended product 1 liter Capacity

Ultracool 12

Normal, Check every 15 hours

Good alternatives

Coolant NF

Normal, Check every 15 hours

#### FRONT FORK

Recommended product Formula GP 5W

Normal, Change every 15 hours

Good alternatives

HPX R 5W

Normal, Change every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.