



Putoline Product recommendation

Husqvarna TC TC 450 (2010-2013)

ENGINE/TRANSMISSION

1,7 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 8 hours

Good alternatives Initial service, Change every 3 hours

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 8 hours

Initial service, Change every 3 hours

HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid

Normal, Check every 4 hours

Good alternatives Normal, Change every 40 hours

DOT 4 Brake Fluid

Normal, Check every 4 hours

Normal, Change every 40 hours

HYDRAULIC CLUTCH SYSTEM, BREMBO

Recommended product Ultimate Racing Brake Fluid

Good alternatives DOT 4 Brake Fluid

HYDRAULIC CLUTCH SYSTEM, MAGURA

Recommended product Formula GP 10W

Normal, Check every 4 hours

Good alternatives Normal, Change every 40 hours

HPX R 10W

Normal, Check every 4 hours

Normal, Change every 40 hours

COOLING SYSTEM

1,1-1,3 liter Capacity

Recommended product Ultracool 12

Normal, Check every 4 hours

Good alternatives Coolant NF

Normal, Check every 4 hours

FRONT FORK, KAYABA

352 CM3 Capacity

Recommended product Formula GP 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product
Good alternatives

FRONT FORK, MARZOCCHI

Formula GP 5W
HPX R 5W

Recommended product
Good alternatives

SHOCK ABSORBER REAR

Formula GP 5W
HPX R 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.