



## Putoline Product recommendation

### KTM 300 300 XC-W (USA) (2010-2012)

Recommended product Good alternatives	<b>ENGINE</b> <u>MX 9</u> <u>MX 7</u> <u>MX 5</u>
Recommended product	<b>TRANSMISSION, 6</b> 0,8 liter Capacity <u>Boxer 4 15W-50, 15W-50</u> Normal, Change every 40 hours/ 280 liter consumed fuel Initial service, Change every 10 hours/ 70 liter consumed fuel <u>N-TECH® Pro R+ Off Road 15W-50, 15W-50</u>
Good alternatives	Normal, Change every 40 hours/ 280 liter consumed fuel Initial service, Change every 10 hours/ 70 liter consumed fuel <u>Ester Tech Off Road 4+ 15W-50, 15W-50</u> Normal, Change every 40 hours/ 280 liter consumed fuel Initial service, Change every 10 hours/ 70 liter consumed fuel
Recommended product	<b>HYDRAULIC BRAKE SYSTEM</b> 0-0 liter Capacity <u>Ultimate Racing Brake Fluid</u> Normal, Change every 12 months Good alternatives <u>DOT 4 Brake Fluid</u> Normal, Change every 12 months <u>DOT 5.1 Brake Fluid</u> Normal, Change every 12 months
Recommended product	<b>HYDRAULIC CLUTCH SYSTEM</b> 0-0 liter Capacity <u>Hydraulic Clutch Fluid</u> Normal, Change every 12 months
Recommended product Good alternatives	<b>COOLING SYSTEM</b> 1,3 liter Capacity <u>Ultracool 12</u> <u>Coolant NF</u>
Recommended product	<b>FRONT FORK</b> 195 CM3 Capacity 365 CM3 Capacity <u>Formula GP 5W, 5W</u> Normal, Change every 40 hours Initial service, Change every 10 hours/ 1 race Good alternatives <u>HPX R 5W, 5W</u> Normal, Change every 40 hours Initial service, Change every 10 hours/ 1 race

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

**SHOCK ABSORBER REAR**

HPX R 2.5W

Normal, Change every 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.