Putoline Product recommendation

Sherco SE SE 250i (2012-2012)

	ENGINE/TRANSMISSION
	0,9 liter Capacity
Recommended product	N-TECH® Pro R+ Off Road 10W-60, 10W-60
	Normal, Change every 20 hours
	Initial service, Change every 5 hours
Good alternatives	Ester Tech Off Road 4+ 10W-60, 10W-60
	Normal, Change every 20 hours
	Initial service, Change every 5 hours
	HYDRAULIC BRAKE SYSTEM
	0-0 liter Capacity
Recommended product	Ultimate Racing Brake Fluid
	Normal, Change every 12 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Change every 12 months
	HYDRAULIC CLUTCH SYSTEM
	0-0 liter Capacity
Recommended product	Ultimate Racing Brake Fluid
	Normal, Change every 12 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Change every 12 months
	COOLING SYSTEM
	1,1 liter Capacity
Recommended product	Ultracool 12
Good alternatives	Coolant NF
	FRONT FORK, SACHS
	600 CM3 Capacity
Recommended product	Formula GP 5W
	Normal, Change every 12 months
Good alternatives	HPX R 5W
	Normal, Change every 12 months
	SHOCK ABSORBER REAR
Recommended product	HPX R 2.5W
	Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.