



Putoline Product recommendation

Suzuki RM(-Z) RM 65 (2003-2006)

Recommended product	ENGINE
	<u>MX 9</u>
	<u>MX 7</u>
Good alternatives	<u>MX 5</u>
	TRANSMISSION, 6
	0,5 liter Capacity
Recommended product	<u>Boxer 4 15W-50</u>
	Normal, Change every 3 races
	<u>N-TECH® Pro R+ 10W-30</u>
Good alternatives	Normal, Change every 3 races
	<u>Sport 4R 10W-30</u>
	Normal, Change every 3 races
	<u>N-TECH® Pro R+ Off Road 10W-40, 15W-50</u>
	Normal, Change every 3 races
	<u>N-TECH® Pro R+ Off Road 10W-50</u>
	Normal, Change every 3 races
	HYDRAULIC BRAKE SYSTEM
	0-0 liter Capacity
Recommended product	<u>Ultimate Racing Brake Fluid</u>
	Normal, Check every 3 races
	Normal, Change every 24 months
Good alternatives	<u>DOT 4 Brake Fluid</u>
	Normal, Check every 3 races
	Normal, Change every 24 months
	COOLING SYSTEM
	0,4 liter Capacity
Recommended product	<u>Ultracool 12</u>
	Normal, Check every 20000 km
	Normal, Change every 60000 km/ 27 months
Good alternatives	<u>Coolant NF</u>
	Normal, Check every 20000 km
	Normal, Change every 60000 km/ 27 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.