Putoline Product recommendation

Arctic Cat Wildcat Wildcat X 1000 (2015-2020)

ENGINE, H2
We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT, (4X4)
0,2 liter Capacity

Recommended product	SP Gear Oil 75W-90, 75W-90
	Normal, Check every 500 miles
	Normal, Change every 2000 miles/ 24 months
	Initial service, Change every 100 miles
Good alternatives	Heavy Gear 80W-90, 80W-90
	Normal, Check every 500 miles
	Normal, Change every 2000 miles/ 24 months
	Initial service, Change every 100 miles

DIFFERENTIAL REAR
0,25 liter Capacity

Recommended product	SP Gear Oil 75W-90, 75W-90
	Normal, Check every 500 miles
	Normal, Change every 2000 miles/ 24 months
	Initial service, Change every 100 miles
Good alternatives	Heavy Gear 80W-90, 80W-90
	Normal, Check every 500 miles
	Normal, Change every 2000 miles/ 24 months
	Initial service, Change every 100 miles

HYDRAULIC BRAKE SYSTEM
0-0 liter Capacity

Recommended product	Ultimate Racing Brake Fluid
	Normal, Change every 24 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Change every 24 months

COOLING SYSTEM
3,3 liter Capacity

Recommended product	Ultracool 12
Good alternatives	Coolant NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.