



## Putoline Product recommendation

### Beta Evo Evo 4T 300 (2015-2016)

#### ENGINE/TRANSMISSION

0,9 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 1000 km/ 40 hours

Good alternatives

Initial service, Change every 5 hours

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 1000 km/ 40 hours

Initial service, Change every 5 hours

#### HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Good alternatives

DOT 4 Brake Fluid

#### HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Good alternatives

DOT 4 Brake Fluid

#### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

#### COOLING SYSTEM

0,6 liter Capacity

Recommended product Ultracool 12

Good alternatives

Normal, Change every 2000 km/ 80 hours

Coolant NF

Normal, Change every 2000 km/ 80 hours

#### FRONT FORK LEFT

125 mm Capacity

Recommended product HPX R 7.5W

Normal, Change every 1000 km/ 40 hours

#### FRONT FORK RIGHT

65 mm Capacity

Recommended product HPX R 7.5W

Normal, Change every 1000 km/ 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

**SHOCK ABSORBER REAR**  
Formula GP 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.