Putoline Product recommendation

BRP Can-Am Maverick Maverick 1000 MAX X ds/rs Turbo (2017-2017)

ENGINE, ROTAX 1000R TURBO
2,2 liter Capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-50, 10W-50
Normal, Change every 3000 km/ 100 hours
Severe, Change every 1500 km/ 50 hours

DIFFERENTIAL FRONT
0,5 liter Capacity

Recommended product
SP Gear Oil 75W-90, 75W-90, 75W-90, 75W-90
Initial service, Check every 3000 km/ 12 months/ 100 hours
Initial service, severe, Check every 1500 km/ 12 months/ 50 hours
Normal, Change every 6000 km/ 200 hours
Severe, Change every 3000 km/ 100 hours

DIFFERENTIAL REAR
We are unable to give a standard recommendation for this component. Please contact our service department.

GEARBOX
We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM
260 CM3 Capacity

Recommended product
Ultimate Racing Brake Fluid,
Normal, Change every 6000 km/ 24 months/ 200 hours
Severe, Change every 3000 km/ 24 months/ 100 hours

Good alternatives
DOT 4 Brake Fluid,
Normal, Change every 6000 km/ 24 months/ 200 hours
Severe, Change every 3000 km/ 24 months/ 100 hours

COOLING SYSTEM
5,05 liter Capacity

Recommended product
Ultracool 12,
Normal, Check every 6000 km/ 200 hours
Severe, Check every 6000 km/ 200 hours
Normal, Change every 12000 km/ 60 months
Severe, Change every 6000 km/ 60 months

Good alternatives
Coolant NF,
Normal, Check every 6000 km/ 200 hours
Severe, Check every 6000 km/ 200 hours
Normal, Change every 12000 km/ 60 months
Severe, Change every 6000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.