



## Putoline Product recommendation

### Gas Gas SM SM 125 (2004-2007)

Recommended product	<b>ENGINE</b> <u>MX 9</u>
Good alternatives	<u>MX 5</u>
	<b>TRANSMISSION MANUAL, 6</b> 0,75 liter Capacity
Recommended product	<u>N-TECH® Pro R+ 10W-30</u> Normal, Change every 29 liter consumed fuel
Good alternatives	<u>Sport 4R 10W-30</u> Normal, Change every 29 liter consumed fuel <u>Off Road 4 10W-40</u> Normal, Change every 29 liter consumed fuel
	<b>HYDRAULIC BRAKE SYSTEM</b> 0-0 liter Capacity
Recommended product	<u>Ultimate Racing Brake Fluid</u> Normal, Change every 24 months
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 24 months
	<b>COOLING SYSTEM</b> 0-0 liter Capacity
Recommended product	<u>Ultracool 12</u> Normal, Change every 24 months
Good alternatives	<u>Coolant NF</u> Normal, Change every 24 months
	<b>FRONT FORK</b>
Recommended product	<u>HPX R 7.5W</u> Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.