

Good alternatives

Putoline Product recommendation

Husqvarna SM SM 400 R (2002-2006)

ENGINE/TRANSMISSION

1,4 liter Capacity

0,1 liter Filter capacity

Recommended product N-TECH® Pro R+ Off Road 10W-60, 10W-60, 10W-60, 10W-60

> Normal, Change every 5000 km Severe, Change every 5 hours

First change only, Change every 1000 km

Severe, first change only, Change every 3 hours

Ester Tech Off Road 4+ 10W-60, 10W-60, 10W-60, 10W-60

Normal, Change every 5000 km Severe, Change every 5 hours

First change only, Change every 1000 km Severe, first change only, Change every 3 hours

HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid,

Normal, Check every 5000 km Severe, Check every 5 hours Normal, Change every 10000 km Severe, Change every 15 hours

Good alternatives DOT 4 Brake Fluid,

Normal, Check every 5000 km Severe, Check every 5 hours Normal, Change every 10000 km Severe, Change every 15 hours

HYDRAULIC CLUTCH SYSTEM

Recommended product Hydraulic Clutch Fluid

COOLING SYSTEM

1.1-1,3 liter Capacity Recommended product Ultracool 12

Good alternatives Coolant NF

FRONT FORK

Recommended product HPX R 7.5W, 7.5W Normal, Change every 10000 km

Severe, Change every 15 hours

SHOCK ABSORBER REAR

Recommended product HPX R 2.5W

> The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.