



Putoline Product recommendation

Husqvarna SM SM 610 S (1999-2003)

ENGINE/TRANSMISSION

2 liter Capacity

Recommended product Ester Tech Off Road 4+ 10W-40, 10W-40
Normal, Check every 1000 km
Normal, Change every 5000 km
First change only, Change every 1000 km/ 6 months

HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid.
Normal, Check every 1000 km
Initial service, Check every 1000 km/ 6 months
Normal, Change every 10000 km

Good alternatives DOT 4 Brake Fluid.
Normal, Check every 1000 km
Initial service, Check every 1000 km/ 6 months
Normal, Change every 10000 km

COOLING SYSTEM

1,35 liter Capacity

Recommended product Ultracool 12.
Normal, Check every 1000 km
Initial service, Check every 1000 km/ 6 months
Normal, Change every 20000 km

Good alternatives Coolant NF.
Normal, Check every 1000 km
Initial service, Check every 1000 km/ 6 months
Normal, Change every 20000 km

FRONT FORK

Recommended product HPX R 7.5W
Normal, Change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.