



Putoline Product recommendation

KTM 65 / 85 / 105 SX 65 SX (2009-2009)

Recommended product Good alternatives	ENGINE, CR 65 <u>MX 9</u> <u>MX 7</u> <u>MX 5</u>
	TRANSMISSION, 6 0,5 liter Capacity <u>Boxer 4 15W-50, 15W-50</u> Normal, Check every 20 hours Normal, Change every 40 hours Initial service, Change every 10 hours/ 1 race
	<u>N-TECH® Pro R+ Off Road 15W-50, 15W-50</u> Normal, Check every 20 hours Normal, Change every 40 hours Initial service, Change every 10 hours/ 1 race <u>Ester Tech Off Road 4+ 15W-50, 15W-50</u> Normal, Check every 20 hours Normal, Change every 40 hours Initial service, Change every 10 hours/ 1 race
Recommended product	HYDRAULIC BRAKE SYSTEM 0-0 liter Capacity <u>DOT 5.1 Brake Fluid</u> Normal, Check every 20 hours Normal, Change every 12 months
	HYDRAULIC CLUTCH SYSTEM <u>Hydraulic Clutch Fluid</u> Normal, Check every 20 hours Normal, Change every 12 months
Recommended product	COOLING SYSTEM 0,55 liter Capacity <u>Ultracool 12</u> Normal, Check every 20 hours Normal, Change every 12 months
	<u>Coolant NF</u> Normal, Check every 20 hours Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

FRONT FORK

Formula GP 5W

Normal, Check every 20 hours

Normal, Change every 12 months

Good alternatives

HPX R 5W

Normal, Check every 20 hours

Normal, Change every 12 months

Recommended product

SHOCK ABSORBER REAR

HPX R 2.5W

Normal, Check every 20 hours

Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.