Putoline Product recommendation

Aprilia RSV RSV 1000 R (2004-2004)

ENGINE/TRANSMISSION

3,9 liter Capacity
0,2 liter Filter capacity

Recommended product
N-TECH® Pro R+ 15W-50, 15W-50, 15W-50
Normal, Change every 10000 km/ 12 months
Initial service, Change every 1000 km
Severe, Change every 5000 km

Good alternatives
Ester Tech 4+ 15W-50, 15W-50, 15W-50
Normal, Change every 10000 km/ 12 months
Initial service, Change every 1000 km
Severe, Change every 5000 km
Sport 4R 15W-50, 15W-50, 15W-50
Normal, Change every 10000 km/ 12 months
Initial service, Change every 1000 km
Severe, Change every 5000 km

HYDRAULIC BRAKE SYSTEM

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km
Normal, Change every 24 months

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km
Normal, Change every 24 months

HYDRAULIC CLUTCH SYSTEM

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km
Normal, Change every 24 months

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km
Normal, Change every 24 months

GREASE POINTS/NIPPLES

Recommended product
White Action Grease + PTFE,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km

Good alternatives
Racing Grease,
Normal, Check every 10000 km/ 12 months
Severe, Check every 5000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

COOLING SYSTEM

2,2 liter Capacity

Recommended product	Ultracool 12,
	Normal, Check every 10000 km/ 12 months
	Severe, Check every 5000 km
	Normal, Change every 24 months
Good alternatives	Coolant NF,
	Normal, Check every 10000 km/ 12 months
	Severe, Check every 5000 km
	Normal, Change every 24 months

FRONT FORK

0,52 liter Capacity

Recommended product	Formula GP 5W, 5W
	Normal, Change every 20000 km
	Initial service, Change every 10000 km
Good alternatives	HPX R 5W, 5W, 20W, 20W
	Normal, Change every 20000 km
	Initial service, Change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.