Putoline Product recommendation

Aprilia Tuono Tuono 1000 R (2004-2005)

ENGINE/TRANSMISSION

3,9 liter Capacity
0,2 liter Filter capacity

Recommended product	N-TECH® Pro R+ 15W-50, 15W-50
	Normal, Change every 10000 km/ 12 months
	Initial service, Change every 1000 km
Good alternatives	Ester Tech 4+ 15W-50, 15W-50
	Normal, Change every 10000 km/ 12 months
	Initial service, Change every 1000 km
	Sport 4R 15W-50, 15W-50
	Normal, Change every 10000 km/ 12 months
	Initial service, Change every 1000 km

HYDRAULIC BRAKE SYSTEM

Recommended product	Ultimate Racing Brake Fluid
	Normal, Check every 10000 km/ 12 months
	Normal, Change every 20000 km/ 24 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Check every 10000 km/ 12 months
	Normal, Change every 20000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

Recommended product	Ultimate Racing Brake Fluid
	Normal, Check every 10000 km/ 12 months
	Normal, Change every 20000 km/ 24 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Check every 10000 km/ 12 months
	Normal, Change every 20000 km/ 24 months

GREASE POINTS/NIPPLES

Recommended product	White Action Grease + PTFE
	Normal, Check every 10000 km/ 12 months
Good alternatives	Racing Grease
	Normal, Check every 10000 km/ 12 months

COOLING SYSTEM

2,2 liter Capacity

Recommended product	Ultracool 12
	Normal, Change every 10000 km/ 12 months
Good alternatives	Coolant NF
	Normal, Change every 10000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

FRONT FORK
0,52 liter Capacity

Recommended product
Formula GP 5W, 5W
Normal, Change every 20000 km
Initial service, Change every 10000 km

Good alternatives
HPX R 5W, 5W, 20W, 20W
Normal, Change every 20000 km
Initial service, Change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.