Putoline Product recommendation

Beta RR RR 4T Enduro 350 (2012-2012)

ENGINE

0,85 liter Capacity

Recommended product
Boxer 4 15W-50, 15W-50
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

Good alternatives
N-TECH® Pro R+ Off Road 15W-50, 15W-50
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

Ester Tech Off Road 4+ 15W-50, 15W-50
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

TRANSMISSION, 6

0,85 liter Capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-40, 10W-40
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

Good alternatives
Ester Tech Off Road 4+ 10W-40, 10W-40
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

Off Road 4 10W-40, 10W-40
Normal, Change every 30 hours/ 200 liter consumed fuel
Initial service, Change every 3 hours/ 20 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Check every 15 hours

Good alternatives
DOT 4 Brake Fluid
Normal, Check every 15 hours

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Check every 15 hours

Good alternatives
DOT 4 Brake Fluid
Normal, Check every 15 hours

COOLING SYSTEM

1,3 liter Capacity

Recommended product
Ultracool 12

Good alternatives
Coolant NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

Recommended product

FRONT FORK
150 mm Capacity
HPX R 2.5W
Normal, Check every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.