



Putoline Product recommendation

Beta RR RR 4T Enduro 390 (2015-2018)

ENGINE

0,75 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 30 hours

Good alternatives

Initial service, Change every 3 hours

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 30 hours

Initial service, Change every 3 hours

TRANSMISSION, 6

1 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-40, 10W-40

Normal, Change every 30 hours

Good alternatives

Initial service, Change every 3 hours

Ester Tech Off Road 4+ 10W-40, 10W-40

Normal, Change every 30 hours

Initial service, Change every 3 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid

Normal, Change every 24 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid

Normal, Change every 24 months

COOLING SYSTEM

1,3 liter Capacity

Recommended product Ultracool 12

Good alternatives

Coolant NF

FRONT FORK

110 mm Capacity

Recommended product HPX R 7.5W

Normal, Check every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.