



## Putoline Product recommendation

### Dinli DL 605 DL 605 - 150 Enforcer

Recommended product	<b>ENGINE</b> <u>Ester Tech Quad RF4+ 10W-40</u>
Good alternatives	Normal, Change every 1000 km/ 6 months/ 30 hours <u>Quad RF4 10W-40</u> Normal, Change every 1000 km/ 6 months/ 30 hours
Recommended product	<b>FINAL REDUCTION</b> <u>SP Gear Oil 75W-90</u>
Good alternatives	Normal, Change every 1000 km/ 6 months/ 30 hours <u>Heavy Gear 80W-90</u> Normal, Change every 1000 km/ 6 months/ 30 hours
Recommended product	<b>HYDRAULIC BRAKE SYSTEM</b> 0-0 liter Capacity <u>DOT 4 Brake Fluid</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.