



Putoline Product recommendation

Ducati Hypermotard 939 Hypermotard (2016-2018)

ENGINE/TRANSMISSION

3,35 liter Capacity

Recommended product

N-TECH® Pro R+ 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 36 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 1000 km/ 6 months

Normal, Change every 36 months

COOLING SYSTEM

2,4 liter Capacity

Recommended product

Ultracool 12

Normal, Check every 15000 km/ 12 months

Normal, Change every 45000 km/ 48 months

Good alternatives

Coolant NF

Normal, Check every 15000 km/ 12 months

Normal, Change every 45000 km/ 48 months

FRONT FORK LEFT

429 CM3 Capacity

Recommended product

ATF

Normal, Change every 45000 km

Good alternatives

Formula GP 5W

Normal, Change every 45000 km

HPX R 5W

Normal, Change every 45000 km

FRONT FORK RIGHT

561 CM3 Capacity

Recommended product

ATF

Normal, Change every 45000 km

Good alternatives

Formula GP 5W

Normal, Change every 45000 km

HPX R 5W

Normal, Change every 45000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.