



Putoline Product recommendation

Ducati Multistrada Multistrada 1200 Enduro Pro (2017-2018)

ENGINE/TRANSMISSION

4,1 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 15000 km/ 12 months

Good alternatives

Initial service, Change every 1000 km/ 12 months

Ester Tech Off Road 4+ 15W-50, 15W-50

Normal, Check every 1000 km/ 6 months

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid.

Normal, Check every 15000 km/ 12 months

Initial service, Check every 1000 km/ 12 months

Normal, Change every 36 months

Good alternatives

Initial service, Change every 36 months

DOT 4 Brake Fluid.

Normal, Check every 15000 km/ 12 months

Initial service, Check every 1000 km/ 12 months

Normal, Change every 36 months

Initial service, Change every 36 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid.

Normal, Check every 15000 km/ 12 months

Initial service, Check every 1000 km/ 12 months

Normal, Change every 36 months

Good alternatives

Initial service, Change every 36 months

DOT 4 Brake Fluid.

Normal, Check every 15000 km/ 12 months

Initial service, Check every 1000 km/ 12 months

Normal, Change every 36 months

Initial service, Change every 36 months

COOLING SYSTEM

2,5 liter Capacity

Recommended product Ultracool 12

Normal, Change every 45000 km/ 48 months

Good alternatives

Coolant NF

Normal, Change every 45000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

FRONT FORK

316-326 CM3 Capacity

752-762 CM3 Capacity

ATF

Normal, Change every 30000 km

Formula GP 5W

Normal, Change every 30000 km

HPX R 5W

Normal, Change every 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.