Putoline Product recommendation

Ducati Multistrada Multistrada 1200 S (2016-2018)

ENGINE/TRANSMISSION

4,1 liter Capacity

Recommended product
N-TECH® Pro R+ Off Road 15W-50, 15W-50
Normal, Check every 1000 km/ 6 months
Normal, Change every 15000 km/ 12 months
Initial service, Change every 1000 km/ 12 months

Good alternatives
Ester Tech Off Road 4+ 15W-50, 15W-50
Normal, Check every 1000 km/ 6 months
Normal, Change every 15000 km/ 12 months
Initial service, Change every 1000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Check every 1000 km/ 6 months
Normal, Change every 36 months

Good alternatives
DOT 4 Brake Fluid
Normal, Check every 1000 km/ 6 months
Normal, Change every 36 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Check every 15000 km/ 12 months
Normal, Change every 36 months

Good alternatives
DOT 4 Brake Fluid
Normal, Check every 15000 km/ 12 months
Normal, Change every 36 months

COOLING SYSTEM

2,5 liter Capacity

Recommended product
Ultracool 12
Normal, Check every 15000 km/ 12 months
Normal, Change every 60000 km/ 48 months

Good alternatives
Coolant NF
Normal, Check every 15000 km/ 12 months
Normal, Change every 60000 km/ 48 months

FRONT FORK ACTIVE

247-257 CM3 Capacity

Recommended product
ATF
Normal, Change every 30000 km

Good alternatives
Formula GP 5W
Normal, Change every 30000 km
HPX R 5W
Normal, Change every 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

FRONT FORK PASSIVE
637-647 CM3 Capacity

Recommended product	ATF Normal, Change every 30000 km
Good alternatives	Formula GP 5W Normal, Change every 30000 km HPX R 5W Normal, Change every 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.