



## Putoline Product recommendation

### KTM 250 250 XC-W (USA) (2010-2012)

|                     |   |
|---------------------|---|
| Recommended product | <b>ENGINE</b><br><u>MX 9</u>  |
| Good alternatives   | <u>MX 7</u><br><u>MX 5</u>  |
| Recommended product | <b>TRANSMISSION, 6</b><br>0,7 liter Capacity<br><u>Boxer 4 15W-50, 15W-50</u><br>Normal, Change every 40 hours/ 280 liter consumed fuel<br>Initial service, Change every 10 hours/ 70 liter consumed fuel   |
| Good alternatives   | <u>N-TECH® Pro R+ Off Road 15W-50, 15W-50</u><br>Normal, Change every 40 hours/ 280 liter consumed fuel<br>Initial service, Change every 10 hours/ 70 liter consumed fuel<br><u>Ester Tech Off Road 4+ 15W-50, 15W-50</u><br>Normal, Change every 40 hours/ 280 liter consumed fuel<br>Initial service, Change every 10 hours/ 70 liter consumed fuel |
| Recommended product | <b>HYDRAULIC BRAKE SYSTEM</b><br>0-0 liter Capacity<br><u>Ultimate Racing Brake Fluid</u><br>Normal, Change every 12 months   |
| Good alternatives   | <u>DOT 4 Brake Fluid</u><br>Normal, Change every 12 months<br><u>DOT 5.1 Brake Fluid</u><br>Normal, Change every 12 months  |
| Recommended product | <b>HYDRAULIC CLUTCH SYSTEM</b><br>0-0 liter Capacity<br><u>Ultimate Racing Brake Fluid</u><br>Normal, Change every 12 months  |
| Good alternatives   | <u>DOT 4 Brake Fluid</u><br>Normal, Change every 12 months<br><u>DOT 5.1 Brake Fluid</u><br>Normal, Change every 12 months  |
| Recommended product | <b>COOLING SYSTEM</b><br>1,2 liter Capacity<br><u>Ultracool 12</u>  |
| Good alternatives   | <u>Coolant NF</u>   |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

#### **FRONT FORK**

620 CM3 Capacity

Formula GP 5W, 5W

Normal, Change every 40 hours

Initial service, Change every 10 hours/ 1 race

Good alternatives

HPX R 5W, 5W

Normal, Change every 40 hours

Initial service, Change every 10 hours/ 1 race

Recommended product

#### **SHOCK ABSORBER REAR**

HPX R 2.5W

Normal, Change every 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.