



Putoline Product recommendation

KTM 450 450 SX-F (2007-2012)

ENGINE/TRANSMISSION

1,35 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50

Normal, Change every 10 hours/ 70 liter consumed fuel

Good alternatives

Initial service, Change every 3 hours/ 20 liter consumed fuel

Ester Tech Off Road 4+ 10W-50, 10W-50

Normal, Change every 10 hours/ 70 liter consumed fuel

Initial service, Change every 3 hours/ 20 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid.

Normal, Check every 10 hours/ 1 race/ 70 liter consumed fuel

Initial service, Check every 3 hours/ 20 liter consumed fuel

Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM, BREMBO

0-0 liter Capacity

Recommended product DOT 5.1 Brake Fluid.

Normal, Check every 10 hours/ 1 race/ 70 liter consumed fuel

Initial service, Check every 3 hours/ 20 liter consumed fuel

Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM, MAGURA

0-0 liter Capacity

Recommended product Hydraulic Clutch Fluid

COOLING SYSTEM

1,2 liter Capacity

Recommended product Ultracool 12.

Normal, Check every 1 race/ 70 liter consumed fuel/ 10 hours

Initial service, Check every 3 hours/ 20 liter consumed fuel

Good alternatives

Coolant NF.

Normal, Check every 1 race/ 70 liter consumed fuel/ 10 hours

Initial service, Check every 3 hours/ 20 liter consumed fuel

FRONT FORK

195 CM3 Capacity

370-380 CM3 Capacity

Recommended product Formula GP 5W

Normal, Change every 12 months

Good alternatives

HPX R 5W

Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.