



Putoline Product recommendation

Suzuki RM(-Z) RM-Z 250 K8/K9 (2008-2009)

ENGINE/TRANSMISSION

1 liter Capacity

0,95 liter Capacity

0,05 liter Filter capacity

Recommended product N-TECH® Pro R+ Off Road 10W-40

Normal, Change every 3 races/ 6 hours

Good alternatives Ester Tech Off Road 4+ 10W-40

Normal, Change every 3 races/ 6 hours

Off Road 4 10W-40

Normal, Change every 3 races/ 6 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Check every 1 race/ 2 hours

Normal, Change every 12 months

Good alternatives DOT 4 Brake Fluid

Normal, Check every 1 race/ 2 hours

Normal, Change every 12 months

COOLING SYSTEM

0,95 liter Capacity

Recommended product Ultracool 12

Normal, Check every 1 race/ 2 hours

Normal, Change every 12 months

Good alternatives Coolant NF

Normal, Check every 1 race/ 2 hours

Normal, Change every 12 months

FRONT FORK

193 CM3 Capacity

370 CM3 Capacity

Recommended product HPX R 4W

Normal, Change every 3 races/ 6 hours

SHOCK ABSORBER REAR

395 CM3 Capacity

Recommended product HPX R 2.5W

Normal, Check every 1 race/ 2 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.