Putoline Product recommendation

Suzuki RM(-Z) RM-Z 450 (2008-2018)

ENGINE/TRANSMISSION

1,2 liter Capacity
1,1 liter Capacity
0,05 liter Filter capacity

Recommended product: N-TECH® Pro R+ Off Road 10W-40
Normal, Change every 3 races/ 6 hours

Good alternatives: Ester Tech Off Road 4+ 10W-40
Normal, Change every 3 races/ 6 hours

Off Road 4 10W-40
Normal, Change every 3 races/ 6 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product: Ultimate Racing Brake Fluid
Normal, Check every 1 race/ 2 hours
Normal, Change every 12 months

Good alternatives: DOT 4 Brake Fluid
Normal, Check every 1 race/ 2 hours
Normal, Change every 12 months

COOLING SYSTEM

0,95 liter Capacity

Recommended product: Ultracool 12
Normal, Check every 1 race/ 2 hours
Normal, Change every 12 months

Good alternatives: Coolant NF
Normal, Check every 1 race/ 2 hours
Normal, Change every 12 months

FRONT FORK

193 CM3 Capacity
370 CM3 Capacity

Recommended product: HPX R 4W
Normal, Change every 3 races/ 6 hours

SHOCK ABSORBER REAR

395 CM3 Capacity

Recommended product: HPX R 2.5W
Normal, Check every 1 race/ 2 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.