Putoline Product recommendation

TM Racing END 300 END (2010 and after)

	ENGINE
Recommended product	MX 9
Good alternatives	MX 7
	MX 5
	TRANSMISSION, 6
	0,7 liter Capacity
Recommended product	RS 75 75/80W, 75-80W, 75-80W, 75-80W
	Normal, Change every 30 hours/ 150 liter consumed fuel
	Initial service, Change every 3 hours/ 15 liter consumed fuel
	Competition, Change every 1 races
	Competition, first service only, Change every 2 hours/ 12 liter consumed fuel
Good alternatives	GP 80 80W, 80W, 80W, 80W
	Normal, Change every 30 hours/ 150 liter consumed fuel
	Initial service, Change every 3 hours/ 15 liter consumed fuel
	Competition, Change every 1 races
	Competition, first service only, Change every 2 hours/ 12 liter consumed fuel
	GP 10 75W, 75W, 75W, 75W
	Normal, Change every 30 hours/ 150 liter consumed fuel
	Initial service, Change every 3 hours/ 15 liter consumed fuel
	Competition, Change every 1 races
	Competition, first service only, Change every 2 hours/ 12 liter consumed fuel
	HYDRAULIC BRAKE SYSTEM
	0-0 liter Capacity
Recommended product	Ultimate Racing Brake Fluid,
	Normal, Change every 12 months
	Competition, Change every 3 races
Good alternatives	DOT 4 Brake Fluid,
	Normal, Change every 12 months
	Competition, Change every 3 races
	HYDRAULIC CLUTCH SYSTEM
	0-0 liter Capacity
Recommended product	Ultimate Racing Brake Fluid,
	Normal, Change every 12 months
	Competition, Change every 3 races
Good alternatives	DOT 4 Brake Fluid,
	Normal, Change every 12 months
	Competition, Change every 3 races

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

COOLING SYSTEM
1 liter Filter capacity

Recommended product	Ultracool 12
Good alternatives	Coolant NF

FRONT FORK, MARZOCCHI
0,3-0,33 liter Capacity

Recommended product	Formula GP 5W
Good alternatives	HPX R 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.