



## Putoline Product recommendation

### TM Racing MX 300 MX (2010 and after)

Recommended product	<b>ENGINE</b> <u>MX 9</u>
Good alternatives	<u>MX 7</u> <u>MX 5</u>
Recommended product	<b>TRANSMISSION, 6</b> 0,7 liter Capacity <u>RS 75 75/80W, 75-80W</u> Normal, Change every 1 races Initial service, Change every 2 hours/ 12 liter consumed fuel
Good alternatives	<u>GP 80 80W, 80W</u> Normal, Change every 1 races Initial service, Change every 2 hours/ 12 liter consumed fuel <u>GP 10 75W, 75W</u> Normal, Change every 1 races Initial service, Change every 2 hours/ 12 liter consumed fuel
Recommended product	<b>HYDRAULIC BRAKE SYSTEM</b> 0-0 liter Capacity <u>Ultimate Racing Brake Fluid</u> Normal, Change every 3 races
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 3 races
Recommended product	<b>HYDRAULIC CLUTCH SYSTEM</b> 0-0 liter Capacity <u>Ultimate Racing Brake Fluid</u> Normal, Change every 3 races
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 3 races
Recommended product	<b>COOLING SYSTEM</b> 1 liter Filter capacity <u>Ultracool 12</u>
Good alternatives	<u>Coolant NF</u>
Recommended product	<b>FRONT FORK, MARZOCCHI</b> 0,32-0,36 liter Capacity <u>Formula GP 5W</u>
Good alternatives	<u>HPX R 5W</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.