



Putoline Product recommendation

TM Racing SMX 660 SMX (2006-2009)

ENGINE/TRANSMISSION

1,4 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50, 10W-50, 10W-50

Normal, Change every 30 hours/ 150 liter consumed fuel

Competition, Change every 1 each race

Competition, first service only, Change every 2 hours/ 12 liter consumed fuel

Good alternatives Normal, first service only, Change every 3 hours/ 15 liter consumed fuel

Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-50, 10W-50

Normal, Change every 30 hours/ 150 liter consumed fuel

Competition, Change every 1 each race

Competition, first service only, Change every 2 hours/ 12 liter consumed fuel

Normal, first service only, Change every 3 hours/ 15 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid,

Normal, Change every 12 months

Competition, Change every 3 races

Good alternatives DOT 4 Brake Fluid,

Normal, Change every 12 months

Competition, Change every 3 races

HYDRAULIC CLUTCH SYSTEM

Recommended product Ultimate Racing Brake Fluid,

Normal, Change every 12 months

Competition, Change every 3 races

Good alternatives DOT 4 Brake Fluid,

Normal, Change every 12 months

Competition, Change every 3 races

COOLING SYSTEM

1,3 liter Capacity

Recommended product Ultracool 12

Good alternatives Coolant NF

FRONT FORK, MARZOCCHI

0,27-0,3 liter Capacity

Recommended product Formula GP 5W

Good alternatives HPX R 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.