Putoline Product recommendation

Aprilia RXV / SXV RXV / SXV 450 (2006-2012)

	ENGINE
	1,3 liter Capacity
Recommended product	N-TECH® Pro R+ Off Road 10W-60, 10W-60, 10W-60, 10W-60
	Normal, Change every 3000 km
	Severe, Change every 15 hours
	First change only, Change every 500 km
	Severe, first change only, Change every 3 hours
Good alternatives	Ester Tech Off Road 4+ 10W-60, 10W-60, 10W-60, 10W-60
	Normal, Change every 3000 km
	Severe, Change every 15 hours
	First change only, Change every 500 km
	Severe, first change only, Change every 3 hours
	TRANSMISSION, 5
Recommended product	N-TECH® Pro R+ Off Road 10W-60
	Normal, Change every 3000 km
Good alternatives	Ester Tech Off Road 4+ 10W-60
	Normal, Change every 3000 km
	HYDRAULIC BRAKE SYSTEM
Recommended product	Ultimate Racing Brake Fluid, , ,
	Normal, Check every 3000 km
	Severe, Check every 15 hours
	First change only, Check every 500 km
	Severe, first change only, Check every 3 hours
	Normal, Change every 12 months
	Severe, Change every 12 months
Good alternatives	DOT 4 Brake Fluid, , ,
	Normal, Check every 3000 km
	Severe, Check every 15 hours
	First change only, Check every 500 km
	Severe, first change only, Check every 3 hours
	Normal, Change every 12 months
	Severe, Change every 12 months
	COOLING SYSTEM
	1,1 liter Capacity
Recommended product	Ultracool 12, , ,
	Normal, Check every 3000 km
	Severe, Check every 15 hours
	First change only, Check every 500 km
	Severe, first change only, Check every 3 hours
Good alternatives	Coolant NF, , ,
	Normal, Check every 3000 km
	Severe, Check every 15 hours
	First change only, Check every 500 km
	Severe, first change only, Check every 3 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

FRONT FORK

Recommended product	Formula GP 10W, 10W
	Normal, Change every 9000 km
	Severe, Change every 45 hours
Good alternatives	HPX R 7.5W, 7.5W, 10W, 10W
	Normal, Change every 9000 km
	Severe, Change every 45 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.