

Good alternatives

## Putoline Product recommendation

## Beta RR RR 4T 250 (2007-2009)

**ENGINE, BETA** 

1,25 liter Capacity

Recommended product | Boxer 4 15W-50, 15W-50

Normal, Change every 15 hours

Initial service, Change every 3 hours

N-TECH® Pro R+ Off Road 15W-50, 15W-50

Normal, Change every 15 hours Initial service, Change every 3 hours Ester Tech Off Road 4+ 15W-50, 15W-50

Normal, Change every 15 hours Initial service, Change every 3 hours

**HYDRAULIC BRAKE SYSTEM** 

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid,

Normal, Check every 15 hours Initial service, Check every 3 hours Normal, Change every 24 months

Good alternatives <u>DOT 4 Brake Fluid,</u>

Normal, Check every 15 hours Initial service, Check every 3 hours Normal, Change every 24 months

**HYDRAULIC CLUTCH SYSTEM** 

0-0 liter Capacity

Recommended product | Hydraulic Clutch Fluid

**COOLING SYSTEM** 

1,3 liter Capacity

Recommended product | <u>Ultracool 12</u>

Normal, Check every 1000 km/ 40 hours

Normal, Change every 3000 km/ 120 hours

Good alternatives Coolant NF

Normal, Check every 1000 km/ 40 hours Normal, Change every 3000 km/ 120 hours

**FRONT FORK** 

0,6 liter Capacity

Recommended product | HPX R 7.5W

Normal, Check every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.