



Putoline Product recommendation

Beta RR RR 4T 450 (2010-2011)

ENGINE

1,25 liter Capacity

Recommended product

Boxer 4 15W-50, 15W-50

Normal, Change every 15 hours

Good alternatives

Initial service, Change every 3 hours

N-TECH® Pro R+ Off Road 15W-50, 15W-50

Normal, Change every 15 hours

Initial service, Change every 3 hours

Ester Tech Off Road 4+ 15W-50, 15W-50

Normal, Change every 15 hours

Initial service, Change every 3 hours

TRANSMISSION, 6

0,8 liter Capacity

Recommended product

N-TECH® Pro R+ Off Road 10W-40

Good alternatives

Ester Tech Off Road 4+ 10W-40

Off Road 4 10W-40

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid,

Normal, Check every 15 hours

Initial service, Check every 3 hours

Good alternatives

Normal, Change every 24 months

DOT 4 Brake Fluid,

Normal, Check every 15 hours

Initial service, Check every 3 hours

Normal, Change every 24 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 15 hours

Normal, Change every 24 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 15 hours

Normal, Change every 24 months

COOLING SYSTEM

1,3 liter Capacity

Recommended product

Ultracool 12

Normal, Check every 1000 km/ 40 hours

Normal, Change every 3000 km/ 120 hours

Good alternatives

Coolant NF

Normal, Check every 1000 km/ 40 hours

Normal, Change every 3000 km/ 120 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

FRONT FORK

0,6 liter Capacity

HPX R 7.5W

Normal, Check every 15 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.