Putoline Product recommendation

Casalini Sulky Sulky (2008-2016)

ENGINE, MITSUBISHI L2C
2,4 liter Capacity

Recommended product	ATV Farm Oil 15W-40, 15W-40
	Initial service, Check every 1000 km
	Normal, Change every 5000 km

FINAL GEAR FRONT, 1/1
0,75 liter Capacity

Recommended product	SP Gear Oil 75W-90
	Normal, Change every 20000 km

HYDRAULIC BRAKE SYSTEM
0,25 liter Capacity

Recommended product	Ultimate Racing Brake Fluid
	Normal, Change every 30000 km/ 24 months
Good alternatives	DOT 4 Brake Fluid
	Normal, Change every 30000 km/ 24 months

COOLING SYSTEM
4,4 liter Capacity

Recommended product	Ultracool 12
	Normal, Change every 30000 km/ 24 months
Good alternatives	Coolant NF
	Normal, Change every 30000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.