Putoline Product recommendation

Gas Gas EC EC 515 (2009-2009)

ENGINE/TRANSMISSION

1,2 liter Capacity

Recommended product
N-TECH® Pro R+ 10W-30, 10W-30
Normal, Change every 30 hours
Initial service, Change every 5 hours

Good alternatives
Sport 4R 10W-30, 10W-30
Normal, Change every 30 hours
Initial service, Change every 5 hours
N-TECH® Pro R+ Off Road 10W-40, 10W-40
Normal, Change every 30 hours
Initial service, Change every 5 hours
Ester Tech Off Road 4+ 10W-40, 10W-40, 15W-50, 15W-50
Normal, Change every 30 hours
Initial service, Change every 5 hours
Off Road 4 10W-40, 10W-40
Normal, Change every 30 hours
Initial service, Change every 5 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Change every 24 months

Good alternatives
DOT 4 Brake Fluid
Normal, Change every 24 months

COOLING SYSTEM

0-0 liter Capacity

Recommended product
Ultracool 12
Normal, Change every 24 months

Good alternatives
Coolant NF
Normal, Change every 24 months

FRONT FORK

Recommended product
Formula GP 5W
Normal, Check every 60 hours

Good alternatives
HPX R 5W
Normal, Check every 60 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.